

version 1.0



2023-2024 Catalogue

Incubator



Innovative Life Sciences Tools

MS Mini Incubator

MO-MINI

Major Science's Mini Incubator is designed for personal use and small laboratories, saving much of space. The unit features a broad temperature range to meet a variety of microbiology or hematology applications. It is compact and economical, featuring unique features. The housing is all corrosion resistant metal. The glass window of the door offers full visibility to the interior. One stainless steel shelf is included, and can be adjusted to two different levels - additional shelves can be purchased to increase storage capacity. The colorful touch panel presents vivid and intuitive user interface and the backlit LED ensures enough brightness even in dark environment.

The heating structure incorporated in MS Mini Incubator performs evenly heating and precise temperature control. The microprocessor ensures temperature stability within the chamber. A thermometer port on the top of the unit allows the users to monitor temperatures.

In addition, a designed spare port is on the rear of the chamber which allows an electrical cord to be routed out if needed. Optional function control software provides real-time data recording through a PC.



Specification

Cat. No.	MO-MINI
Display	LCD
Temperature Range	Ambient +5° to 70°C
Temperature Accuracy	± 0.2°C @ 37°C in center point
Capacity	17L
Exterior Dimension (WxLxH)	Approx. 12.2"x12"x15" (310x306x380mm)
Interior Dimension (WxLxH)	Approx. 10.3"x10"x10" (261x255x255mm)
Weight	Approx. 28.7 (13kg)
Power	100-240V~, 50/60Hz, 2A
Material	Corrosion resistant metal
PC Connection	USB

Ordering Information


Cat. No	Product Description
MO-MINI	MS Mini Incubator with one stainless steel shelf

Accessories

Cat. No	Product Description
MO-SH2524	250x240mm stainless steel shelf for MS Mini Incubator
MO-MINI-SW	Functional control software for MS Mini Incubator, including a USB cable

Features

- Ideal for microbiology or hematology applications
- Corrosion resistant metal housing
- Door with large viewing area
- Backlit colored touched panel
- One stainless steel shelf is included
- Function control software available



MO-SH2524



* All images are for reference only, actual products might differ from the pictures above.
* Technical specifications subject to change without notice.

MS Oven

MO-A01

Major Science's Oven incubator features a broad thermostatic control range and precise temperature uniformity to fulfill a variety of cell culturing and hematology applications. The compact size and stackable design save valuable lab space and maximize productivity. The built-in color touch screen provides hassle-free system operation and instance glance over experiments. With implemented safety features, the powerful MS Oven incubators assure a safe environment to the user as well as samples.

Features

- Large touch screen: 3.5" color display
- Temperature uniformity and accuracy: $\pm 0.2^{\circ}\text{C}$ at 37°C
- Broad temperature control range: ambient $+5^{\circ}\text{C}$ to 85°C
- User temperature calibration
- Safety door switch
- Timer with alarm function
- Power failure auto recovery
- Sturdy, stackable construction



MO-A01

MS Hybridization Oven

MO-AOR

MS Hybridization Oven series is the advanced version of MS Oven and is designed to equip with built-in rotisserie function. MO-AOR is embedded with orbital shaking platform and is ideal for nucleic acid hybridization and incubation such as Southern, Northern, and Western blot. Full accessories are also available upon request to meet different applications.

Features

- Built-in rotisserie function
- Orbital shaking motion
- Large touch screen: 3.5" color display
- Temperature uniformity and accuracy: $\pm 0.2^{\circ}\text{C}$ at 37°C
- Broad temperature control range: ambient $+5^{\circ}\text{C}$ to 85°C
- User temperature calibration
- Safety door switch
- Timer with alarm function
- Power failure auto recovery
- Sturdy, stackable construction



MO-AOR




Model Selection Guide



Cat. No.	MO-A01	MO-AOR
Rotisserie Function	N/A	Yes
Rotisserie Speed / Inc.	N/A	5-100rpm / 1rpm
Shaker Motion	N/A	Orbital clockwise / counterclockwise
Shaker Speed	N/A	0-200rpm

Max. set of flask holder

Flask	MO-AOR
50ml	8
125ml	8
250ml	5
500ml	2



Specification

Cat. No.	MO-A01	MO-AOR
Display	3.5" 64K color TFT display	
Controller	32-bits Microprocessor	
Control Interface	Touch screen & graphical interface	
Rotisserie Function	N/A	Yes
Rotisserie Speed / Inc.	N/A	5 - 100rpm / 1rpm
Timer	9999 (min) with alarm / Continuous	
Shaker Motion	N/A	Orbital clockwise / counterclockwise
Shaker Speed	N/A	0 - 200rpm
Temperature Control Range	Ambient +5°C to 85°C	
Temperature Increment	0.1°C	
Temperature Uniformity	± 0.2°C at 37°C	
Temperature Accuracy	± 0.2°C at 37°C	
User Temperature Calibration	Yes	
Inner Chamber Dimensions (WxLxH)	Approx. 13.4"x8.9"x10.2" (340x225x260mm)	
Inner Chamber Volume	Approx. 5.28gal (20L)	
Dimension (WxLxH)	Approx. 17.4"x18.2"x17.8" (442x462x452mm)	
Platform (WxL)	N/A	Approx. 10.6"x7.9" (270x200mm)
Data Logging	RS-232	
Weight	Approx. 52.9lb (24kg)	Approx. 63.9lb (29kg)
Rated Voltage	110 / 220V~ 50 / 60Hz (Selectable)	
Construction	Painted iron metal with ABS front door	
Safety Device	Safety door switch	
	Thermal safety switch	
	Auto shut off upon fan failure	
	Power failure auto recovery	

Ordering Information

Cat. No	Product Description
MO-A01	MS Oven with 2 layers of stainless steel mesh plates and 8 plate holders
MO-AOR	MS Hybridization/Orbital Shaking Oven (without rotisserie), 110 / 220V~


Accessories

Cat. No	Product Description
MO-01-PF	1 layer of stainless steel mesh plate with 4 plate holders
MO-HY-8RT	40mm tube rotisserie for 8 tubes
MO-HY-16RT	50ml conical tube rotisserie for 16 tubes
MO-HY-24RT	15ml conical tube rotisserie for 24 tubes
MO-P2320	Additional 230x200mm platform for orbital and reciprocal shaker (with 4 of 100mm pillars)
SI-200-08	Flask Holder, 50ml
SI-200-09	Flask Holder, 125ml
SI-200-10	Flask Holder, 250ml
SI-200-11	Flask Holder, 500ml
MO-BT40x150	Glass tube 40x150mm (diameter x length)
MO-BT40x200	Glass tube 40x200mm (diameter x length)
MO-BT40x300	Glass tube 40x300mm (diameter x length)

- Various accessories available
- Note each accessory do not apply to all the models of MS oven. Please visit our website at www.majorsci.com for more details.



Touch screen & graphical control interface



* All images are for reference only, actual products might differ from the pictures above.
* Technical specifications subject to change without notice.



Taiwan Headquarters

Headquarters:

No. 156, Sec. 1, Guoji Rd., Taoyuan Dist.,
Taoyuan City 33061, Taiwan
T/+886-3-3762878
F/+886-3-3761310

Factory:

No.19, Ln. 207, Huakang St. Bade Dist.,
Taoyuan City 33464 Taiwan
T/ +886-3-3623319
F/ +886-3-3623133
Email : info@majorsci.com

US Office

19959 Sea Gull Way
Saratoga, CA 95070
U.S.A.
T/ +1-408-366-9866
F/ +1-408-446-1107

Shanghai Office

Room 612, International business exhibition center,
9300 Hunan Road, Pudong, Shanghai, China
National toll-free No.:400-823-9177
T/ +86-21-50795277
F/ +86-21-50795277

India Office

D. No. 12-13-99, Satguru Apts. Extn.
Street. No. 3, Lane No.1, Tamaka
Secunderabad – 500 017. India
T/ +91-40-27001515
T/ +91-40-27001586



www.majorsci.com

info@majorsci.com

